

## H2280S-M

Maximize the Performance of your LXE® 2280-2285 Series Hand-held Scanners.



The H2280S-M is a direct replacement for the OEM P/N 155467-0001 battery that is used in the LXE® 2280-2285 Series Hand-held Scanners.

### Features:

- Contains the highest quality battery cells.
- Provides excellent discharge characteristics.
- Provides longer cycle life.
- Extends operating time and reduces the total number of batteries needed.
- Rigorous testing including temperature, vibration, shock, drop, short circuit, and overcharge.

### Cell Specifications:

|            |           |
|------------|-----------|
| Chemistry: | NiMH      |
| Voltage:   | 7.2 volts |
| Capacity:  | 1000 mAh  |

### Battery Dimensions:

|         |                         |
|---------|-------------------------|
| Width : | 1.330 inches (33.7 mm)  |
| Length: | 4.445 inches (112.9 mm) |
| Height: | 0.686 inches (17.4 mm)  |

### Warranty:



Each battery is guaranteed to be free from defects in materials and workmanship and can maintain a minimum of 80% of its rated capacity for 12 months from date of shipment under normal use.

### About Us

Global Technology Systems, Inc. is a recognized leader in the design, development and manufacture of battery packs, chargers and power management technology for portable and mobile devices and systems.

Our batteries are relied upon by Fortune 500 businesses, Homeland Security, and public safety agencies to power mission critical communication and mobile computing applications.

### For Pricing or Additional Information Contact:

Global Technology Systems, Inc.  
550 Cochituate Road  
Framingham, MA 01701  
800.267.2711  
In Europe call: 00800.5390.5390  
[www.GTSpower.com](http://www.GTSpower.com)

