

HCH-9060-CHG

Compact and Versatile Six Bay Charger for MC9000 Series Devices

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to +40°C
Storage Range: -10°C to +50°C

Dimensions:

Width: 6.3 inches (160 mm)
Length: 30 inches (660 mm)
Height: 3.5 inches (89 mm)
without batteries or device inserted.
Weight: 5.6 lb (2500 g)

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries:

HMC9000-Li(24) Honeywell® Battery

- Highest quality cells used.
- Longer cycle life.
- Extremely rugged.
- Rigorous testing.



Trademarks are the sole property of their respective owners.
The Honeywell® Trademark is used under license from Honeywell® International Inc.

11.09.12

Made of highly rugged aerospace grade aluminium housing.

Includes power supplies and cable.

Dual-chemistry charger
Supports Li-Ion and Li-Polymer chemistries.



More charging in less space
Charges 50% more batteries in same space as OEM charger.

Tri-color charging indications
A charging LED indicates charging status.



Hassle-free mounting
Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
800.267.2711 ■ In Europe call: 00800.5390.5390
www.GTSPower.com