

Patriot® DC Charger

Travel Charger for Motorola® XTS3000/5000 Series Radio

Charger Specifications:

- Input Voltage: 12 Volt DC
- Temperature: Operating: -5°C to 55°C (4°F to 130°F)
- Charge Time: 2.5-5 hrs maximum, depending on battery capacity.
- Charge Current: 1300 mA in Constant Current Charge phase.
- Charge Method: Constant Current and/or Constant Voltage with multiple end-of charge termination methods, temperature controlled.

Dimensions:

- Width: 2.6 inches (66.04 mm) does not include power cord
- Length: 3 inches (76.2 mm)
- Height: 2.25 inches (57.15 mm)
- Weight: 0.425 lbs (0.193 Kg)

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 12 months from date of shipment under normal use.



Compatible Batteries:

- H8610-LiP(41) NEOCELL® Battery
- H8299-M(21) Honeywell® Battery
- H8299-M(40) Honeywell Battery
- H7144-M(27) Honeywell Battery
- H7144-C Honeywell Battery
- H8294-C Honeywell Battery

- Highest quality cells used.
- Longer cycle life.
- Extremely rugged.
- Rigorous testing.



Trademarks are the sole property of their respective owners. The Honeywell® Trademark is used under license from Honeywell® International Inc.

11-10-13

Lightweight, versatile and portable design for in-vehicle use.

Radios can be placed in the charger in the 'off' mode, standby mode, operating-receiving mode, or operating-transmitting mode.

Multi-chemistry charger

Supports LiP, Li-Ion, NiCd and NiMH chemistries.

Rapidly charges batteries in 2.5 to 5 hours.

Charges battery alone or while attached to radio.

Hassle-free mounting with available vehicle mount

Includes power supplies and cable.



Tri-color charging indications

A charging LED indicates charging status.



For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
 550 Cochituate Road Framingham, MA 01701
 800.267.2711 ■ In Europe call: 00800.5390.5390
www.GTSpower.com