

Patriot® 1

Single Bay Multi-Chemistry Battery Charger for Motorola® XTS3000/5000 Series

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to +55°C
 (+32°F to +130°F)
 Storage Range: 0°C to +49°C
 (+32°F to +122°F)

Dimensions:

Width: 4.5 inches (114 mm)
 Length: 5 inches (127 mm)
 Height: 3 inches (76 mm)
 Weight: 0.5 lbs (0.25Kg)

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries:

- H8610-LiP(41) NEOCELL® Battery
- H8610-Li(40) Honeywell® Battery
- H8299-M(21) Honeywell Battery
- H8299-M(40) Honeywell Battery
- H7144-M(27) Honeywell Battery
- H7144-C Honeywell Battery
- H8294-C Honeywell Battery

- Highest quality cells used.
- Longer cycle life.
- Extremely rugged.
- Rigorous testing.



Trademarks are the sole property of their respective owners.
 The Honeywell® Trademark is used under license from Honeywell® International Inc.

11.11.15

Light-weight, versatile and portable design for desktop or DC in-vehicle use.

Multi-chemistry charger

Supports LiP, Li-Ion, NiCd and NiMh chemistries.

Rapidly charges batteries in 2.5 to 5 hours.

Charges battery standalone or while attached to radio.

Includes AC and DC power supplies and cables.



Tri-color charging indications

A charging LED indicates charging status.



For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
 550 Cochituate Road Framingham, MA 01701
 800.267.2711 ■ In Europe call: 00800.5390.5390
www.GTSPower.com