

Patriot® 6

Six Bay Multi-Chemistry Battery Charger for EF Johnson® 5100 Series Radio

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to +55°C
(+32°F to +130°F)
Storage Range: 0°C to +49°C
(+32°F to +122°F)

Dimensions:

Width: 5 inches (127 mm)
Length: 18 inches (457.2 mm)
Height: 3.5 inches (89 mm)
Weight: 5 lbs (2.27 Kg)

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries:

- H8610-LiP(41) NEOCELL® Battery
- H8610-Li(40) Honeywell® Battery
- H8299-M(21) Honeywell Battery
- H8299-M(40) Honeywell Battery
- H7144-M(27) Honeywell Battery
- H7144-C Honeywell Battery
- H8294-C Honeywell Battery

- Highest quality cells used.
- Longer cycle life.
- Extremely rugged.
- Rigorous testing.



Trademarks are the sole property of their respective owners.
The Honeywell® Trademark is used under license from Honeywell® International Inc.

11.11.15

Light-weight, versatile and portable design for desktop or DC in-vehicle use.

Multi-chemistry charger

Supports LiP, Li-Ion, NiCd and NiMh chemistries.

Rapidly charges batteries in 2.5 to 5 hours.

Charges battery standalone or while attached to radio.



Hassle-free mounting

Includes power supply and cable.

Tri-color charging indications

A charging LED indicates charging status.



For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
800.267.2711 ■ In Europe call: 00800.5390.5390
www.GTSpower.com